

## Vehicle Wrap Maintenance:

### Power Washing:

Wrapped vehicles may be power-washed or pressure washed, but with care. Excessive pressure during power washing can damage the graphics by allowing water to soak underneath the adhesive vinyl and lessen its adhesion to the vehicle, causing lifting, peeling and/or curling.

These problems are magnified by climate conditions (ie: wind, temperature, rain, etc). When dealing with perforated window film these issues are magnified.

To avoid edge lifting or other damage to the vinyl, follow these guidelines:

- Use a spray nozzle with a 40° wide spray pattern
- Be sure the spray nozzle includes a nozzle protector or tip guard
- Use a pressure system of 2000 psi or less
- If the system is heated, limit the water temperature to 180° or less
- Hold the nozzle at least 12" away from vehicle
- Avoid spraying against the overlaps on the graphics

*Do not use any Automatic Car Washes with Brush Systems. The brushes can catch any loose or peeling edges and cause further damage, as well as dull and scratch the finish on the wrap.*

### Hand Washing Exterior Graphics:

Flush the graphics clean with water to remove loose dirt particles. Avoid using ammonia and/or bleach-based cleaners. (i.e.: Windex, Fantastic, 409, etc).

Use a mild detergent (no solvents) and water solution and wash with a soft brush, rag or sponge.

Wash thoroughly from top to bottom while avoiding unnecessary scrubbing.